


TL15

series



Product Segments

• Ergo Motion


TiMOTION's TL series lifting columns are specifically designed for use in ergonomic desks and work tables. Using multiple TL series lifting columns with compatible TC series Control Boxes and TH/TDH series controls, work surfaces can be controlled quietly and smoothly with synchronous movement. All Ergo Motion TC series control boxes have a less than 0.1W standby power option that reduces power consumption. Our wide range of columns offer customers the solutions they require to satisfy their working environment project requirements. The TL15 has a two stage telescopic outer tube that is designed for a narrow-top, wide-bottom rectangular appearance.

General Features

Max. load	800N (push)
Max. speed at max. load	28mm/s
Max. speed at no load	46mm/s
Retracted length	645mm
Dimension of outer tube	80*60mm rectangular
Stages	2-stage
Stroke	500mm
Output signals	Hall sensor * 2
Voltage	24V DC
Color	Black, white, grey, or special colors
Product Weight	8.2kg /column

Drawing

Standard Dimensions
(mm)



Load and Speed

CODE	Load (N)	Self Locking Force (N)	Typical Current (A)		Typical Speed (mm/s)	
	Push		No Load 32V DC	With Load 24V DC	No Load 32V DC	With Load 24V DC
Motor Speed (5200RPM)						
A	800	800	2.5	5.0	46.0	28.0


Note

- 1 Above self lock performance needs working with TiMOTION control system.
- 2 Parameters above are from tested average, please refer to approval drawing for final value.


Performance Data (24V DC Motor)

Motor Speed (5200RPM)

Speed vs. Load



Current vs. Load




Note

1 The performance data in the curve charts shows theoretical value.

TL15 Ordering Key

TL15

Version: 20260123-F



Appearance of Tubes See page 5	B = With wiper fixing holes at sides	C = Without wiper fixing holes at sides
Voltage	2 = 24V	
Load and Speed See page 2		
Stroke & Retracted Length (mm) See page 5		
Color	1 = Black, RAL 9005, black wiper 2 = Grey, RAL 9006, black wiper 3 = White, RAL 9016, black wiper 4 = Special grey, RAL 9022, black wiper 6 = Grey, RAL 9006, grey wiper	7 = White, RAL 9016, white wiper 8 = Special grey, RAL 9022, grey wiper B = Matte black, RAL 7021, Black wiper C = Graphite grey, RAL7024, Black wiper D = Matte black, RAL 7021, Matte Black wiper
Motor Housing Step	0 = With	1 = Without
Output Signals	2 = Hall sensor * 2	
Plug See page 5	1 = DIN 6P, 90° plug	E = Molex 8P, plug, standard
Cable Length (mm)	1 = Straight, 500	3 = Straight, 1000 4 = Straight, 1500
Bracket	0 = Without L = Left, standard	R = Right, standard 5 = Left, triangle 6 = Right, triangle



Note

¹ The TL is designed especially for push applications, not suitable for pull applications.

Appearance of tubes

B = With wiper fixing holes at sides

C = Without wiper fixing holes at sides



Stroke & Retracted Length (mm)


Foot Assembly	Stroke/Retracted Length
	Standard
Standard	500/645
With Shoes	500/665

Note


1 Only specific TEK could be with the shoes, please refer to TEK speccode

Connector

1 = DIN 6P, 90° plug



E = Molex 8P, plug, standard



Terms of Use

The user is responsible for determining the suitability of TiMOTION products for a specific application. TiMOTION products are subject to change without prior notice.