

TL30S

series



Product Segments

• Ergo Motion

TiMOTION's TL30S series lifting columns are specifically designed for use in ergonomic desks and work tables. Using multiple TL series lifting columns with compatible TC series control boxes and TH / TDH series controls, work surfaces can be controlled quietly and smoothly with synchronous movement. All Ergo Motion TC series control boxes have a less than 0.1W standby power option that reduces power consumption. Our wide range of columns offers customers the solutions they require to satisfy their project requirements.


The TL30S has a two stage telescopic outer tube that is designed for a narrow-top, wide-bottom rectangular appearance.

General Features

Maximum load	600N in push
Maximum speed at full load	24mm/s (with 600N in a push condition)
Minimum installation dimension	645mm
Stroke	500mm
Dimension of outer tube (L*W)	90*60mm
Color	Black, white, grey, or special colors
Two stage outer tube with rectangular appearance	
Narrow top and wide bottom configuration	

Drawing

Standard Dimensions
(mm)



Load and Speed

CODE	Load (N)	Self Locking Force (N)	Typical Current (A)		Typical Speed (mm/s)	
	Push		No Load 32V DC	With Load 24V DC	No Load 32V DC	With Load 24V DC
Motor Speed (5200RPM)						
B	600	600	2.0	4.2	40.0	24.0


Note

- 1 Above self lock performance needs working with Timotion control system.
- 2 Please refer to the approved drawing for the final authentic value.


Performance Data (24V DC Motor)

Motor Speed (5200RPM)

Speed vs. Load



Current vs. Load



Appearance of Tubes	C = Without wiper fixing holes at sides		
Voltage	2 = 24V DC		
Load and Speed	See page 2		
Stroke & Retracted Length (mm)	See page 5		
Color	1 = Black, RAL 9005, Black wiper 2 = Grey, RAL 9006, Black wiper 3 = White, RAL 9016, Black wiper 4 = Special grey, RAL 9022, Black wiper 6 = Grey, RAL 9006, Grey wiper	7 = White, RAL 9016, White wiper 8 = Special grey, RAL 9022, Grey wiper B = Matte black, RAL 7021, Black wiper C = Graphite grey, RAL7024, Black wiper D = Matte black, RAL 7021, Matte Black wiper	
Motor Housing Step	0 = With	1 = Without	
Output Signals	2 = Hall sensor * 2		
Plug See page 5	1 = DIN 6P, 90° plug	E = Molex 8P, plug, standard	
Cable Length (mm)	1 = Straight, 500	3 = Straight, 1000	4 = Straight, 1500
Bracket	0 = Without		

Note

¹ The TL is designed especially for push applications, not suitable for pull applications.

Stroke & Retracted Length (mm)

Foot Assembly	Standard
----------------------	----------

Standard	500 / 645
-----------------	-----------


With shoes	500 / 665
-------------------	-----------

Note


1 Only specific TEK could be with the shoes, please refer to TEK speccode.

Connector

1 = DIN 6P, 90° plug




E = Molex 8P, plug, standard



Appearance of tubes

C = Without wiper fixing holes at sides



Terms of Use

The user is responsible for determining the suitability of TiMOTION products for a specific application. TiMOTION products are subject to change without prior notice.