

# TP4

## series



#### **Product Segments**

### Care Motion


#### **General Features**


Transformer type Input voltage


Maximum output Plug support Color Certificate EI, Toroidal, or SMPS 110V AC, 120V AC, 230V AC, or 100~240V AC (SMPS) 30V DC, 5A EU, USA, AUS, UK, or JPN Black or grey IEC60601-1 and ES60601-1

#### Drawing

Standard Dimension (mm)









## **TP4** Ordering Key



Version: 20131122-E

TP4

| Voltage            | 1 = 110V AC  | 2 = 120V AC | 3 = 230V AC           | 4 = 100~240V AC (SMPS) |
|--------------------|--|-------------|-----------------------|------------------------|
| Plug               | 1 = EU   | 3 = AUS     | 5 = JPN               |                        |
|                    | 2 = USA  | 4 = UK      | A = Others            |                        |
| Color              | 1 = Black  |             | 2 = Grey (Pantone 428 | C)                     |
| Cable Length       | 0 = AC cable: straight, 4000mm; DC cable: straight, 150mm (mount on TC8) |             |                       | A = Customized         |
|                    | 1 = AC cable: straight, 2000mm; DC cable: straight, 1000mm               |             |                       |                        |
|                    | 2 = AC cable: straight, 4000mm; DC cable: straight, 1000mm               |             |                       |                        |
| Grounding Function | 0 = Without  |             | 1 = With              |                        |
|                    |  |             |                       |                        |